

tango

Accuracy and efficacy across three key treatment modalities

CAPSULOTOMY
IRIDOTOMY

Helping the world see clearly

Tango[™] – excellent results, every time

Whether you're seeking to treat glaucoma, or you're performing capsulotomy or iridotomy procedures, $Tango^{T}$, with its fully featured SLT laser and its powerful, precise YAG laser, will enable you to secure the results you and your patients are looking for — consistently and to the highest standard.

Choose Tango[™] from Ellex, and you'll be able to move effortlessly between SLT and YAG modes, which means you can treat patients with glaucoma and secondary cataract with maximum accuracy and optimal efficacy.

Three key treatment options

Choose Tango[™], and you can select from three treatment modalities, which comprise:

SELECTIVE LIGHT THERAPY (SLT) (SELECTIVE LASER TRABECULOPLASTY)

CAPSULOTOMY

IRIDOTOMY



SLT; primary therapy for effective, proven glaucoma treatment

Tango[™] incorporates Ellex's proprietary SLT technology — providing superior energy control, a sharp-edged aiming beam and the industry's fastest firing rate of three shots per second^{*}.

It's a solution that, when used as a first-line therapy, can reduce IOP as effectively as medication without the associated side effects or compliance problems*.

Treat Glaucoma - naturally

Specify Tango™, and you can deliver SLT to stimulate the eye's natural healing response to manage your glaucoma patients' IOP without the burn and scar tissue associated with argon laser trabeculoplasty (ALT). It can also eliminate the issues of compliance and side effects associated with medications.

Evaluate pathology

Not only does SLT offer a highly effective treatment option for glaucoma, but it can also be employed to help estimate the location of the pathology. If intervention with SLT is successful, the primary obstruction region may lie within the trabecular meshwork, but if it is ineffective, then the primary obstruction may reside distal to the trabecular meshwork.

Seamless pairing with MIGS

SLT delivered by Tango™ pairs seamlessly with all MIGS procedures, including ABiC™ performed with Ellex's iTrack™ surgical system, as both a preoperative diagnostic aid or as a postoperative adjunct, and can be deployed synergistically to reduce the need for further medication or future filtration surgery.

^{*} Based on system performance testing. Data on file. Ellex Medical.

[&]quot;Katz LJ, Steinmann WC, Kabir A, Molineaux J, Wizov SS, Marcellino G; SLT/Med Study Group. Selective laser trabeculoplasty versus medical therapy as initial treatment of glaucoma; a prospective, randomized trial. J Glaucoma. 2012;21:460-8

Accurate, effective capsulotomy

Tango's YAG mode features an Ultra Gaussian beam profile and fast rise time. That means you can perform capsulotomies and iridotomies at lower, more efficient energy levels.

With less energy delivered into the eye, you'll be able to carry out capsulotomies with all types of IOLs and with significantly less risk of lens pitting*.

Precision in incision

Ellex's unique YAG laser cavity within Tango™ can typically achieve the industry's lowest energy optical breakdown at 1.8 mJ in air". This allows the energy to form a tight plasma ball, and results in less energy dispersion into surrounding tissue.

IOL-friendly photodisruption

Tango™ focuses more energy into the center of the beam profile to deliver greater energy density — reducing the energy needed to effectively perform capsulotomy and consequently greatly reducing the risk of lens pitting.

Precision caspsulotomy

Choose Tango™ and you'll achieve new levels of capsulotomy accuracy — a perfectly centered and precise capsulotomy that won't affect bag tension or the IOL's visual axis position.

^{*} Based on system performance testing.

^{**}Average performance only. Based on system performance testing. Data on file. Ellex Medical.

Specifications

SLT Mode	YAG Mode
Q-switched, frequency doubled Nd:YAG	Q-switched Nd:YAG
green: 532 nm	infrared: 1064 nm
0.3 to 2.6 mJ per pulse, continuously variable	0.3 to 10 mJ per pulse, continuously variable
3 ns	4 ns
single pulse only	1, 2 and 3 pulses per burst, selectable
400 μm	8 µm
<3 degrees	16 degrees
not applicable	0, ± 100 to 500 μm, continuously variable
	Q-switched, frequency doubled Nd:YAG green: 532 nm 0.3 to 2.6 mJ per pulse, continuously variable 3 ns single pulse only 400 µm <3 degrees

Common Features Specification

Repetition Rate	up to 3 Hertz
Aiming Beam	red 635 nm, adjustable intensity
Magnification	optimized for enhanced anterior segment visualization
Cooling	air cooled
Electrical Requirements	100–240 VAC, 50/60 Hz, 800 VA
Weight	31 kg, 68 lbs (laser only)
Dimensions (HxWxD)	57 x 75 x 44 cm, 23 x 30 x 18 inches (laser only)
Standard Accessories	Total Solution™ tables, remote display, safety glasses, laser safety sign, dust cover
Optional Accessories	Tonometer mount, SLT laser lens, capsulotomy and iridotomy laser lenses, footswitch, five-position magnification changer, beam splitter, "C" mount camera adapter, video camera adapter, co-observation tube



A highly accurate two-point focusing system with a tolerance range of ± 8 µm in YAG mode delivers pinpoint precision.

tango



Find out how Tango™ will help you set new standards in SLT for glaucoma and for capsulotomy and iridotomy.

Contact us now to schedule a demonstration

Head Office

3 Second Avenue Mawson Lakes, SA, 5095 AUSTRALIA +61 8 7074 8200

Registered Office

82 Gilbert Street Adelaide, SA, 5000 AUSTRALIA +61 8 7074 8200

Helping the world see clearly

Ellex Inc. (USA)

7138 Shady Oak Road Minneapolis, MN, 55344 USA 800 824 7444

Ellex iTrack

41316 Christy Street Fremont, CA, 94538 USA 800 391 2316

Ellex Deutschland GmbH

ZPO floor 1, Carl-Scheele-Str.16 12489 Berlin GERMANY +49 30 6392896 00

Ellex France SARL

La Chaufferie – 555 chemin du bois 69140 Rillieux la Pape FRANCE +33 4 8291 0460

Ellex Inc. (Japan)

Harumi Center Bldg 5F, 2-5-24 Harumi Chuo-ku Tokyo 104-0053 JAPAN +81 3 5859 0470

Ellex Australia

3 Second Avenue Mawson Lakes, SA, 5095 AUSTRALIA +61 8 7074 8200

LASER CLASS 2 Diode Lease: 835mm, <1mW Max CW
WARNING - VISIBLE AND INVISIBLE LASER
RADIATION - AVOID EXPOSURE TO BEAM